

Selection Chart



ALBALUCE

CUBE Series Square

Product Image		CCT - Color Temperature (k)			Colour Finish			
		2700			Frame		Reflector	
		3000 (S)				Black		
		3500			White (W)		White	
		4000 (S)					Matt White	
		6000						
		Tunable White						
Geometry Image		Geometry			Selection Technical Parameters			
		Diameter [in mm]	Cutout [W] [in mm]	Height [H] [in mm]	Optics [°]	Wattage [W]	Lumens [lm]	LED Current [mA]
		75	65	61	25[S] 60[FL]	7.5 11	1100 1400	250 350
		110	100	79	60[FL]	9 13	1400 1700	250 350
		167	150	100	70[FL]	18 25	2400 3400	500 700
		220	200	132	70[FL]	25 38	3200 4500	700 1050
Reference Images								
Driver Control Compatibility	Glare Diffusion Diagram		Standard Parameter					
Type			IP Rating	44		54		
Non Dimmable			Adjustability	Fixed				
Phase Dimming			Frame Type	Trim [T]				
1-10V Dimming			Input Parameter	230V - AC				
DALI Dimming			Output Parameter	Constant Current DC				
<p> FAMILY: AL- CUBE - DAIMETER: XX - FRAME TYPE: -FRCD- - FRAME COLOR: T W - OPTIC: NFL CCT: 30K - LED POWER: 11W - CONTROL MODE: SW - IP RATING: 44 </p>								

S - Standard