

# Selection Chart



ALBA

Cube Series

Square

Product Image		CCT - Color Temperature (k)			Colour Finish			
		2700			Frame		Reflector	
		3000 (S)				Black		
		3500			White (W)		White	
		4000 (S)				Matt White		
		6000						
Tunable White								
Geometry Image		Geometry			Selection Technical Parameters			
		Diameter [in mm]	Cutout [W] [in mm]	Height [H] [in mm]	Optics [°]	Wattage [W]	Lumens [lm]	LED Current [mA]
		75	65	61	25[S] 60[FL]	7.5 11	1100 1400	250 350
		110	100	79	60[FL]	9 13	1400 1700	250 350
		167	150	100	70[FL]	18 25	2400 3400	500 700
		220	200	132	70[FL]	25 38	3200 4500	700 1050
Reference Images								
Driver Control Compatibility	Glare Diffusion Diagram 	Standard Parameter						
Type		IP Rating	44		54			
Non Dimmable		Adjustability	Fixed					
Phase Dimming		Frame Type	Trim [T]					
1-10V Dimming		Input Parameter	230V - AC					
DALI Dimming		Output Parameter	Constant Current DC					
FAMILY: AL- CUBE - XX -FRCD- T W - NFL 30K - 11W - SW - 44 DAIMETER: XX FRAME TYPE: T W FRAME COLOR: NFL OPTIC: 30K CCT: 11W LED POWER: SW CONTROL MODE: 44 IP RATING: 44								
S - Standard								