

Selection Chart



ALBALUCE

MINARO Series - Adjustable Twin

Geometry Image		CCT - Color Temperature (k)			Colour Finish			
		2700			Frame		Reflector	
		3000 (S)			Black (B)		Black	
		3500			White (W)		White	
		4000 (S)			Ring Unit  			
		6000						
Tunable White								
Product Image		Geometry			Selection Technical Parameters			
		Diameter [in mm]	Cutout [W] [in mm]	Height [H] [in mm]	Optics [°]	Wattage [W]	Lumens [lm]	LED Current [mA]
		85	75	55	24[S] 40[NFL]	4	400	700
		Diameter [in mm]	Cutout [W] [in mm]	Height [H] [in mm]	Optics [°]	Wattage [W]	Lumens [lm]	LED Current [mA]
		85	75	55	24[S] 40[NFL]	4	400	700
Driver Control Compatibility	Trimless Kit		Standard Parameter					
Type			IP Rating		20		44	
Non Dimmable			Adjustability		25° Rotation			
			Frame Type		Trim [T]			
			Input Parameter		230V - AC			
			Output Parameter		Constant Current DC			
<p>FRAME TYPE</p> <p>SERIES</p> <p>T - TWIN F - FLAT C - CURVE</p> <p>FRAME COLOR</p> <p>OPTIC</p> <p>CCT</p> <p>LED POWER</p> <p>CONTROL MODE</p> <p>IP RATING</p> <p>AL- F DOT -FRCD- T W - S 30K - 4W - SW - 44</p>								
S - Standard								