

Selection Chart



ALBALUCE

SOLIX Series Round

Product Image		CCT - Color Temperature (k)			Colour Finish		
		2700		Frame		Reflector	
		3000 (S)		Black (B)		Black	
		3500		White (W)		White	
		4000 (S)				Matt White	
		6000				Chrome Black	
		Tunable White				Gold	
Geometry Image		Geometry			Selection Technical Parameters		
		Diameter [in mm]	Cutout [in mm]	Height [in mm] [H]	Wattage [W]	Lumens [lm]	LED Current [mA]
		45	45	60	4	350	350
		68	75	98	7.5 11	600 800	250 350
		98	105	128	13 18 25	850 1100 2800	350 500 700
		125	130	159	18 25	1300 1700	500 700
		150	150	190	25 38	1800 2500	700 1050
		Driver Control Compatibility				Standard Parameter	
				IP Rating	20	44	54
Type				Adjustability	Fixed [F]	Adjustable[A]	Washer [W]
Non Dimmable				Frame Type	Trim [T]	Trimless [TL]	
Phase Dimming				Optics [°]	20 [S]	40 [NFL]	50 [FL]
1-10V Dimming				Input Parameter	230V - AC		
DALI Dimming				Output Parameter	Constant Current DC		
Optional Accessories							
Trimless Kit - US		Trimless Kit - EU		Honey Comb Mesh		Frosted Glass	
<p> MOUNTING: AL- ADJUSTABLE: T ROUND: R DAIMETER: A FRAME TYPE: XX FRAME COLOR: -FRCD- OPTIC: TL CCT: W LED POWER: NFL CONTROL MODE: 30K IP RATING: - 11W - SW - 44 </p>							

S - Standard