

# Selection Chart



ALBALUCE

SOLIX Series Square

Product Image		CCT - Color Temperature (k)			Colour Finish		
		2700			Frame		Reflector
		3000 (S)			Black (B)		Black
		3500			White (W)		White
		4000 (S)					Matt White
		6000					Chrome Black
		Tunable White					Gold
Geometry Image		Geometry			Selection Technical Parameters		
		Diameter [in mm]	Cutout [in mm] [DIA]	Height [in mm] [H]	Wattage [W]	Lumens [lm]	LED Current [mA]
		45	45	60	4	350	350
		68	73	98	7.5 11	600 800	250 350
		98	108	128	13 18	850 1100	350 500
		125	132	159	18 25	1300 1700	500 700
		150	150	190	25 38	1800 2500	700 1050
Driver Control Compatibility				Standard Parameter			
				IP Rating	20	44	54
Type				Adjustability	Fixed [F]	Adjustable[A]	Washer [W]
Non Dimmable				Frame Type	Trim [T]	Trimless [TL]	
Phase Dimming				Optics [ ° ]	20 [S]	40 [NFL]	50 [FL]
1-10V Dimming				Input Parameter	230V - AC		
DALI Dimming				Output Parameter	Constant Current DC		
Optional Accessories							
Trimless Kit - US		Trimless Kit - EU		Honey Comb Mesh		Frosted Glass	
<p>             MOUNTING: AL-              ADJUSTABLE: T R A -              DAIMETER: XX              FRAME TYPE: -FRCD- TL W -              FRAME COLOR: NFL              OPTIC: 30K              CCT: -              LED POWER: 11W -              CONTROL MODE: SW -              IP RATING: 44         </p>							

S - Standard