

Selection Chart



ALBALUCE

CLARIO Series

Product Image		CCT - Color Temperature (k)			Colour Finish			
		2700			Frame		Reflector	
		3000 (S)			Black		Black	
		3500			White (W)		White (W)	
		4000 (S)					Silver	
		6000					Specular	
		Tunable White						
Geometry Image		Geometry			Selection Technical Parameters			
		Diameter [in mm]	Cutout [W] [in mm]	Height [H] [in mm]	Optics [°]	LED Wattage [W]	System Wattage [W]	Lumens [lm]
		115	100	90	60[FL]	8 11	10 13	1300 1800
		168	150	99	60[FL]	12 18 24	14 20 26	1900 2700 3500
		220	200	116	60[FL]	26 30	28 33	3900 4600
Specular Reflector		Silver Reflector		White Reflector		Black Reflector		
Driver Control Compatibility	Glare Diffusion Diagram	Standard Parameter						
Type		IP Rating	20		54			
Non Dimmable		Adjustability	Fixed					
Phase Dimming		Frame Type	Trim [T]					
1-10V Dimming		Input Parameter	230V - AC					
DALI Dimming		Output Parameter	Constant Current DC					
<p>CLARIO SERIES: S4 - FOR 115 MM DIA, S6 - FOR 168 MM DIA, S8 - FOR 220 MM DIA</p> <p>FRAME TYPE: S4, S6, S8</p> <p>FRAME COLOR: FRCD</p> <p>OPTIC: T, W, FL</p> <p>CCT: 30K</p> <p>LED POWER: 8W</p> <p>CONTROL MODE: SW</p> <p>IP RATING: 20</p> <p>Example Code: AL- C S4 -FRCD- T W - FL 30K - 8W - SW - 20</p>								

S - Standard