

Selection Chart



ALBA

DOT Series - Fixed

Product Image		CCT - Color Temperature (k)			Colour Finish			
	<p>Flat Curve</p>	2700		Frame		Reflector		
		3000 (S)		Black (B)		Black		
		3500		White (W)		White		
		4000 (S)				Gold		
		6000				Silver		
		Tunable White						
Geometry		Geometry		Selection Technical Parameters				
		Diameter [in mm]	Cutout [W] [in mm]	Height [H] [in mm]	Optics [°]	Wattage [W]	Lumens [lm]	LED Current [mA]
<p>FLAT [F]</p>		40	35	52	18[S] 30[NFL]	1.5	160	500
<p>DIA</p>		50	45	62	30[NFL]	6	600	350
		Diameter [in mm]	Cutout [W] [in mm]	Height [H] [in mm]	Optics [°]	Wattage [W]	Lumens [lm]	LED Current [mA]
<p>CURVE [C]</p>		40	35	52	18[S] 30[NFL]	1.5	160	500
<p>DIA</p>		50	45	62	30[NFL]	6	600	350
Driver Control Compatibility				Standard Parameter				
Type	Non Dimmable			IP Rating	20	44		
Reflector Combination for Flat Version Only				Adjustability	Fixed			
White	Black	Gold	Silver	Frame Type	Trim [T]			
				Input Parameter	230V - AC			
				Output Parameter	Constant Current DC			
<p>FRAME TYPE FRAME COLOR OPTIC CCT LED POWER CONTROL MODE IP RATING</p> <p>SERIES</p> <p>T - TWIN F - FLAT C - CURVE</p> <p>AL- F DOT -FRCD- T W - S 30K - 4W - SW - 44</p>								

S - Standard