

Selection Chart



ALBA

DOT Series - Adjustable Twin

Geometry Image		CCT - Color Temperature (k)			Colour Finish				
		2700			Frame		Reflector		
		3000 (S)			Black (B)		Black		
		3500			White (W)		White		
		4000 (S)			Ring Unit				
		6000					Black	White	
Tunable White									
Product Image		Geometry			Selection Technical Parameters				
		Diameter [in mm]	Cutout [W] [in mm]	Height [H] [in mm]	Optics [°]	Wattage [W]	Lumens [lm]	LED Current [mA]	
		85	75	55	24[S] 40[NFL]	4	400	700	
		Diameter [in mm]	Cutout [W] [in mm]	Height [H] [in mm]	Optics [°]	Wattage [W]	Lumens [lm]	LED Current [mA]	
		85	75	55	24[S] 40[NFL]	4	400	700	
Driver Control Compatibility	Trimless Kit 		Standard Parameter						
Type			IP Rating		20		44		
Non Dimmable			Adjustability		25° Rotation				
			Frame Type		Trim [T]				
			Input Parameter		230V - AC				
			Output Parameter		Constant Current DC				
<p> SERIES: T - TWIN, F - FLAT, C - CURVE FRAME TYPE: AL- FRAME COLOR: DOT - FRCD- OPTIC: T, W, S CCT: 30K LED POWER: 4W CONTROL MODE: SW IP RATING: 44 </p>									
S - Standard									