


NEW

FAIRY C

Garden Light



Black

**Drawing**

Order Options

FAIRY S100 CV

Code	System LM	LED W	System W	Input Voltage	CRI	CCT	Beam
FAIRY S100 C CV-82230	260 /390lm	4W	5W	24V DC	80	2200/3000K	130°

FAIRY S100 HV

Code	System LM	LED W	System W	Input Voltage	CRI	CCT	Beam
FAIRY S100 C HV-82230	300 /460lm	6W	7W	220-240VAC	80	2200/3000K	130°



Features

- Modular designed pathway light with IP66 waterproof rating, perfect for outdoor use
- TWist&Lock covers are interchangeable, styles can be custom made
- Press button for CCT changeable, warm 2200K or cozy 3000K
- Extension poles are available with shrubbery growing
- Multiple installation accessories; Pole, Spike or base mounting
- Triple layer coating, ensuring over 1000hours of salt mist test, suitable for seaside installations
- 24VDC or 220-240VAC input are optional
- Wider light distribution 120° achieved by advanced lens design
- Invisible screws for esthetic appeal
- 5 years warranty

Specifications

- Input Voltage: 24VDC/220-240VAC
- Beam angle: 130°
- Physical: Die-casting, Powder coating

Type



pathlight

Light distribution



Accessory

**MT01**

Pole spike

For soft soil

**MT02**

Spike with pedal

For hard soil

**MT03**

Base

For wood or concrete

**EP300**

Extension Pole 300mm

Length can be tailored