

Selection Chart



ALBALUCE

Iris Series

		CCT - Color Temperature (k)			Colour Finish				
					Frame			Reflector	
		2700			Black (B)			Black	
		3000 (S)			White (W)			White	
		3500			X	Customised			
4000 (S)									
6000									
Geometry Image		Selection Technical Parameters			Optic [°]				
		System Watt [W]	Wattage [W]	Lumens [lm]	Spot [S]	Wide Spot [WS]	Narrow Flood [NFL]	Flood [NFL]	
		2 1-LED	1.6	140	15	25	40	-	
		4.8 3-LED	4.3	420	15	-	40	60	
		11.5 7-LED	11	1100	20	30	-	60	
Driver Control Compatibility			Standard Parameter						
			IP Rating IK Rating		67 08				
			Type	Adjustability		Adjustable [A] - 180° Adjustment			
			Non Dimmable	CRI		90		80	
			1-10V Dimming	Input Parameter		230V - AC			
DALI Dimming	Output Parameter		Constant Voltage DC - 24V						
Optional Accessories									
Stake Unit		Clear Glass - Standard			Frosted Glass				
<p>LED POWER</p> <p>FAMILY FINISH COLOR OPTIC CCT CONTROL MODE IP RATING</p> <p>AL- IRIS - FRG - T B - S 30K - 12W - SW - 67</p>									

S - Standard