

Selection Chart



ALBALUCE

Solar Series

Product Image		CCT - Color Temperature (k)			Colour Finish		
		2700		Frame		Reflector	
		3000 (S)		Black (B)		Black	
		3500		White (W)		White	
		4000 (S)		X	Customised		
		6000					
Geometry Image		Selection Technical Parameters			Optic [°]		
		System Watt [W]	Wattage [W]	Lumens [lm]	Spot [S]	Wide Spot [WS]	Narrow Flood [NFL]
		5.5	5	550	-	30	45
		10	9	900	20	30	50
		18	16	2100	18	-	-
Driver Control Compatibility		Standard Parameter					
		IP Rating IK Rating			66 08		
Type		Adjustability		Adjustable [A] - 180° Adjustment			
Non Dimmable		CRI		90	80		
1-10V Dimming		Input Parameter		230V - AC			
DALI Dimming		Output Parameter		Constant Voltage DC - 24V			
Optional Accessories							
Stake Unit		Clear Glass - Standard			Glare Guard for 5.5W & 10W		
<div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="text-align: center;"> <p>FAMILY</p> <p>AL- SOLAR - FRG - T</p> </div> <div style="text-align: center;"> <p>FINISH COLOR</p> <p>B - S</p> </div> <div style="text-align: center;"> <p>OPTIC</p> </div> <div style="text-align: center;"> <p>CCT</p> <p>30K - 12W - SW - 67</p> </div> <div style="text-align: center;"> <p>LED POWER</p> </div> <div style="text-align: center;"> <p>CONTROL MODE</p> </div> <div style="text-align: center;"> <p>IP RATING</p> </div> </div>							

S - Standard