

Selection Chart



ALBALUCE

Track Linear Adjustable Series

Product Image		CCT - Color Temperature (k)		Colour Finish		
		2700		Frame		Code
		3000 (S)		Black		B
		3500		White		W
		4000 (S)		Custom Colour		X
		6000				
Geometry Image		Selection Technical Parameters				
Length [in mm][L]	Width[W] X Height[H] [in mm]	System Watt -> lm	Optics [°]	Wattage [W]	Lumens [lm]	Operation Mode
283		7 - 450	110 [FL]	6	650	48V - DC
		13 - 1200	20 [NS] 35 [S]	12	1600	
Wall Washer Units - Optic Diffused						
290		7 - 420	65 [FL]	6	650	48V - DC
570		7 - 450	110 [FL]	6	650	
Driver Control Compatibility & Optional Accessories		Standard Parameter				
		IP Rating		20	44	
Type	Microprismatic Cover	Adjustability		Fixed [F]		
Non Dimmable		Frame Type		Trim [T]		
Phase Dimming		Input Parameter		230V - AC		
1-10V Dimming		Output Parameter		Constant Voltage DC - 48V		
DALI Dimming		Driver Dimension		18mm H x 190mm L		
<p> LENGTH OF THE LIGHT FRAME TYPE FRAME COLOR LED POWER WATTAGE OPTIC CCT CONTROL MODE IP RATING (BLANK FOR 20) </p> <p> ALA - WITHOUT DIFFUSER GLA - PC DIFFUSER CLA - MICROPRISMATIC DIFFUSER WW - WALL WASHER SERIES </p> <p> AL- ALA 283 - FRCTX - T B - FL 30K - 6W - SW - 44 </p>						
S - Standard						