Selection Chart

ALBALUCE

Track Pendent Series

Product Image	CCT - Color Temperature (k)	Colour Finish		
	2700	Frame		Code
	3000 (S)	Black		B
	3500	White		W
	4000 (S)	Custom Colour		X
	6000			

Geometry Image		Selection Technical Parameters				
Daimenter [D] X Height[H] [in mm]		System Watt -> lm	Optics [°]	Wattage [W]	Lumens [lm]	Operation Mode
55 x 110 [H]		14 - 1000	18 [NS] 24 [S] 36 [WS]	13	1300	48V - DC
40 x 400 [H]		12 - 800	18 [NS] 30 [S] 45 [WS]	11	1100	
300 X 180 [H]		18 - 700	60 [FL]	17	1400	
300 X 180 [H]		18 - 800	60 [FL]	17	1400	

Driver Control Compatibility & Optional Accessories		Standard Parameter			
		IP Rating	20	44	
Type	Microprismatic Cover	Adjustability	Fixed [F]		
Non Dimmable		Frame Type	Trim [T]		
Phase Dimming		Input Parameter	230V - AC		
1-10V Dimming		Output Parameter	Constant Voltage DC - 48V		
DALI Dimming		Driver Dimension	18mm H x 190mm L		

DIAMETER
FRAME TYPE
FRAME COLOR
OPTIC
LED POWER WATTAGE
PL - PENDENT SERIES
CONTROL MODE
CCT
IP RATING (BLANK FOR 20)

AL- PL 300 - FRCTX - T B - FL 30K - 17W - SW - 44

S - Standard