

Selection Chart

ALBALUCE

2216 Series



Product Image	CCT - Color Temperature (k)		Led Module	San-An Chip			
	2700						
	3000 (S)						
	3500						
	4000 (S)						
	6000						
Geometry Parameters		Selection Technical Parameters - Per metre					
Geometry Image	Cutting Length [in mm]	LEDs	Wattage [W]	Lumens [lm]	Efficiency [lm / W]	PCB Width [in mm]	
	25	160	7	1300	130	4	
	25	280	10	1100	110	8	
	25	320	19	3000	160	10	
	Free Cutting	300	7	1300	186	5	
	Free Cutting	300	10	1300	130	8	
	Free Cutting	300	15	1950	130	10	
 		Standard Parameter					
		IP Rating		20	44	55	
				65	67	68	
		CRI		80+	90+		
		Input Parameter		24V - DC (12V DC Available)			
		Dimmable		Yes			
		Standard Packing		5 mtr Roll			
Maximum Length		15 Mtrs for 24V - 10 Mtrs for 12V					
<p>LED COUNT LED POWER WATTAGE VOLTAGE PCB WIDTH IP RATING (BLANK FOR 20)</p> <p>2216 - SERIES CCT</p> <p>AL- 2216 300 - 7W - 24V - W4 - 30K - 65</p> <p>S - Standard</p>							