








Selection Chart

ALBALUCE

2835 Series



Product Image	CCT - Color Temperature (k)		Led Module	San-An Chip			
	2700			2216 SMD			
	3000 (S)						
	3500						
	4000 (S)						
	6000						
Geometry Parameters		Selection Technical Parameters - Per metre					
Geometry Image	Cutting Length [in mm]	LEDs	Wattage [W]	Lumens [lm]	Efficiency [lm / W]	PCB Width [in mm]	
	100	60	5	600	120	8	
	50	180	10	2000	215	10	
	50	120	10	1200	120	8	
	100	120	10	1000	100	10	
	50	160	14	2000	160	10	
	33	240	24	4000	180	10	
     		Standard Parameter					
		IP Rating		20	44	55	
				65	67	68	
		CRI		80+	90+		
		Input Parameter		24V - DC (12V DC Available)			
		Dimmable		Yes			
		Standard Packing		5 mtr Roll			
Maximum Length		15 Mtrs for 24V - 10 Mtrs for 12V					
<p>LED COUNT LED POWER WATTAGE VOLTAGE PCB WIDTH CCT IP RATING (BLANK FOR 20)</p> <p>2835 - SERIES 240 24W 24V W10 30K</p> <p>AL- 2835 240 - 24W - 24V - W10 - 30K -</p> <p>S - Standard</p>							