


Product Photo



→ Reinforced 1515 SMD LED inside



Key Feature

Product Advantages

- ▶ Reinforced 1515 SMD LED inside
- ▶ Reinforced 2-OZ (25/50um) PCBs
- ▶ Excellent Linear Lighting performance
- ▶ Always same BIN for different batches
- ▶ Comply with all kinds of waterproof solutions
- ▶ Free-cutting Design
- ▶ Max. 10m in series connection with power at one end

Basic Parameters

Power	10W/meter
Voltage	DC-24V optional
Current/M	0.42A/m@24V
PCB	8mm width
Max. Connect	5m with Power-Feed at one end

Optical Parameters

CRI	CRI>90
Lumen	1080 LM/m
Efficiency	90 LM/watt
LED Type	280pcs 1515 SMD LEDs
LED Chips	Epistar/San-An

Customized Options

PCB color Options	White/Black/Brown
PCB thickness	2-OZ/3-OZ/4-OZ
Waterproof	IP-20/IP-55/IP-65/IP-67/IP-68
Viewing Angle	170°
Packing/roll	5m/10m/20m/50m



CCT / COLOR Solution

2000K	2700K	3000K	3500K	4000K	4500K	6000K	9000K
SS	SW	WW	WN	NW	SN	CW	SC

Waterproof Solution

No	Shrink	Nano	Drop	Extrusion	PU fill
IP-20	IP-44	IP-55	IP-65	IP-67	IP-68

Part No.	LEDs/m	Power	Voltage	Width	CCT
AL-SCOB-2.7K-280-10W-W8-R90	280-LEDs/m	10W/m	DC-24V	8mm	2700K
AL-SCOB-3K-280-10W-W8-R90	280-LEDs/m	10W/m	DC-24V	8mm	3000K
AL-SCOB-4K-280-10W-W8-R90	280-LEDs/m	10W/m	DC-24V	8mm	4000K
AL-SCOB-6K-280F-10W-W8-R90	280-LEDs/m	10W/m	DC-24V	8mm	6000K

