

Selection Chart

ALBALUCE

Micro Flex Series



Product Image		CCT - Color Temperature (k)			Led Module		San-An Chip			
		2700 3000 (S) 3500 4000 (S) 6000								
Geometry Parameters			Selection Technical Parameters - Per metre							
Geometry Image	Overall Dimension XX x YY [in mm]	Bending	LEDs	Wattage [W]	Lumens [lm]	Efficiency [lm / W]	Width [in mm]			
	04 x 10	Side	320	7.2	240	33	4			
	03 x 06	Side	240	9	270	30	3			
	03 x 06T	Side	240	9	270	30	3			
	06 x 06	Verticle	256	7	410	58	6			
	03 x 05	Verticle	256	7	780	110	5			
	06 x 12	Side	120	14	710	50	6			
				Standard Parameter						
				IP Rating		-	54	67		
				CRI		80+	90+			
				Input Parameter		24V - DC				
				Dimmable		Yes				
				Standard Packing		5 mtr Roll				
Maximum Length		15 Mtrs for 24V								
<p>OVERALL DIMENSION XXYY</p> <p>NEON - SERIES</p> <p>LED POWER WATTAGE</p> <p>VOLTAGE</p> <p>CCT</p> <p>IP RATING</p> <p>AL- N F 0606 - 7W - 24V - 30K - 67</p>										

S - Standard