

Selection Chart



ALBALUCE

M - Trim - Round

Selection Chart

Geometry Image		CCT - Color Temperature (k)			Colour Finish			
		2700		Frame			Reflector	
		3000 (S)		Black (B)			Black	
		3500		White (W)			White	
		4000 (S)					Matt White	
		6000					Chrome Black	
		Tunable White (TW)					Gold	
Module Selection		Selection Technical Parameters			Optic Parameters Availability			
L50 - 7.5W L50 - 11W	L50 - 13W	Wattage [W]	Lumens [lm]	LED Current [mA]	15° [S]	25° [WS]	35° [NFL]	60° [FL]
Height = 44mm	Height = 65mm	7.5	950	250	Yes	Yes	Yes	Yes
		11	1300	350	Yes	Yes	Yes	Yes
		13	1600	350	Yes	Yes	Yes	Yes
Driver Control Compatibility		Standard Parameter						
		IP Rating			20	44	54	65
Type	Lens / Glare Accessories	Mounting Ring	Refer Below Images					
Non Dimmable - SW	Honey Comb - HC	Frame	Trim [T]			Trimless [TL]		
Phase Dimming - PH	Linear Spread - LC	Shape - Cut out	DIA - 75mm		EU - 75MM	US - 77MM		
1-10V Dimming - DI	Frosted Glass - FG	Input Parameter	230V - AC					
DALI Dimming - DA	Diffuser Lens - DIF	Output Parameter	Constant Current DC					
Dayton-Vr1		Dot-Vr2		Comet-Vr3		Eye-Vr4		
Ring-Vr5		Wall Washer - WW		Double Spot - DS		Trimless Version only Cut Out = 147 x 75 mm		
<p> FAMILY: AL- MTRIM: -FRCD- RING TYPE: VR1 FRAME TYPE: T S FRAME COLOR: NFL OPTIC: 30K CCT: 11W LED POWER: SW CONTROL MODE: 44 IP RATING: </p>								
S - Standard		TW - Tunable White ONLY						