

Selection Chart



ALBALUCE

M - Trim - Square Selection Chart

Geometry Image		CCT - Color Temperature (k)			Colour Finish			
		2700			Frame		Reflector	
		3000 (S)			Black (B)		Black	
		3500			White (W)		White	
		4000 (S)					Matt White	
		6000					Chrome Black	
		Tunable White (TW)			Gold			
Module Selection		Selection Technical Parameters			Optic Parameters Availability			
L50 - 7.5W L50 - 11W	L50 - 13W	Wattage [W]	Lumens [lm]	LED Current [mA]	15° [S]	25° [WS]	35° [NFL]	60° [FL]
Height = 44mm	Height = 65mm	7.5	950	250	Yes	Yes	Yes	Yes
		11	1300	350	Yes	Yes	Yes	Yes
		13	1600	350	-	Yes	Yes	Yes
Driver Control Compatibility		Standard Parameter						
		IP Rating	20	44	54	65		
Type	Lens / Glare Accessories	Mounting Ring	Refer Below Images					
Non Dimmable - SW	Honey Comb - HC	Frame	Trim		Trimless			
Phase Dimming - PH	Linear Spread - LC	Shape - Cut out	DIA - 75mm	SQ - 75mm	DIA - 75mm	SQ - 80mm		
1-10V Dimming - DI	Frosted Glass - FG	Input Parameter	230V - AC					
DALI Dimming - DA	Diffuser Lens - DIF	Output Parameter	Constant Current DC					
Core-Cr1		Minimo-Cr2		Double Spot - CDS				
				Trimless Cut Out = 147 x 80 mm				
Opticore-Cr4				Double Spot - CDS				
				Trim Cut Out = 145 x 75 mm				
<p>FAMILY: AL- RING TYPE: MTRIM FRAME COLOR: -FRCD- FRAME TYPE: CR1 OPTIC: T S CCT: - NFL LED POWER: 30K CONTROL MODE: 11W IP RATING: - SW - 44</p>								
S - Standard		TW - Tunable White ONLY						